


# GREAVES POWER TILLER





# GREAVES

### POWER TILLER

#### **Product Specifications:**

Greaves GS-15 DIL model power tiller fitted with 14.6 hp 2000 rpm DI Diesel engine (4- stroke single cylinder horizontal water cooled radiator type) strong chassis and trouble free gear box and transmission system. Most suitable for cultivation of paddy, various crops, orchards, Tea/coffee gardens, Interculture cultivation in grape vines, horticulture, sugarcane fields etc. For wetland and dry land cultivation in plain as well as hilly areas.

#### **ENGINE**

Bore X Stroke : 100 X 115 mm

Displacement : 903 cc Compression : 20:1

2 Hr Rating : 11 kw/2000 rpm

12-Hr Rating : 10.9 Kw/2000 rpm

SFC : 268 gm/kw/hr

LPH : 1.5

LOC : 0.78 gm/kw/hr

Dry wt : 160 kg

Fuel tank Capacity: 16 Lit.

Cooling water : 5 Lit.

Oil capacity : 3.6 Lit.

Air cleaner : 3 stage oil bath type

Lubrication : Combined pressure

With splashing

Starting : Hand cranking

#### **TILLERS**

L x W x H : 2990 x 980 x 1270

Gross wt : 515 Kg

Clutch : Double Disc constant

contact

Brake : Internal expanding

wet type

Tilling speed : First 2-speeds

Rotovator : Provided

No. of tynes : 20

Final Transmission : Double chain

Sitting Arrangement: Detachable type

Wheel size : 6.00-12

Wheel Tread : 800 mm (std)

Wheel Pressure : 137-196 Kpa

Loading capacity : 1.5-2 Tonnes

#### **PERFORMANCE**

Tilling width : 600 mm

Tilling depth : 150 mm

Tilling rate : 0.138 ha/hr

Ground clearance: 170 mm (min)

Speed (km/hr)

6 forward : 1.53 to 16.70

2 Reverse : 1.1 & 4.21

Rotary speed High

speed : Two h : 300 RPM

Low : 188 RPM

Transmission

Efficiency: 90%

Kw at rotary : 10.1


Standard accessories comprise of one iron tail wheel, one wheel changer and one tool kit. One pair of cage wheel optional.





Power Tiller has the following equipment attached to for your advantage and profits. Plougher (dry & wet) used for alternating of soil at a depth of 12" by interchangeable double plough.

Tiller: Used for pulverizing of soil both in dry & wet land by means of straight and bend tynes attached to the rotary. Ridger: Used for making dyke in the field after cultivation for vegetables or orchards. Ditcher: Used for making narrow drain in the field after cultivation. Leveller: Leveller is attached to it for covering the soil. Seed driller: Used for sowing seeds with manure. Sprayer: Used for spraying medicine in the field as and when required. Pump: Used for drawing water from well or river to irrigate the field. Harvester: Used for harvesting paddy, wheat, bajra, jowar etc. Thrasher: Used for separating grain from plant after harvesting. Flour mill: Used for making flour from grain. Generator: Used for generating current approx 7.5 kv for lighting, pumping etc. Stone cutter: Used for cutting of laterite stone, sold as a brick. Weeder: Used to clear weeds in the field which in turn forms composite manure.



Two speed rotary shaft

High transmission efficiency

Faster & deeper tilling

Economy in operation

Rugged construction Easy spare parts availability Prompt after sales service



## **Greaves Cotton Limited**

BUSINESS GROUP II: AGRO EQUIPMENT GROUP

KOLKATA:

**GREAVES SINCE 1859** 

PETROL ENGINE UNIT, Post Box No. 892,0Id Mahabali puram Road, Thoraipakkam, Chennai 600 096. Phone: (91-44) 24961539, 24960485 • Fax: (91-44) 24960721 • E-mail: bg2hq@greavesmail.com. HEAD OFFICE:

REGIONAL OFFICE: Industry Manor, Appasaheb Marathe Marg, Prabhadevi, Mumbai-400 025. Phone: (91-22) 24223747/24365510 • Fax: (91-22) 24367785/24379555. MUMBAI:

Express Building Annexe, 9-10, Bahadur Shah Zafar Marg, New Delhi-110 002. Phone: (91-11) 23730554 • Fax: (91-11) 23359782, 23357739 NEW DELHI:

Thapar House, 25, Brabourne Road, Kolkota-700 001.
Phone: (91-33) 22424316/17/20/21, 22423805, 22438815, 22420817 • Fax: (91-33) 22424325 CHENNAI:

Wavoo Mansion, 6th Floor, New No. 48 (Old No. 39) Rajaji Salai, Chennai 600 001. Phone: (91-44) 25255200 • Fax: (91-44) 25224557